



- **Resistenza alle alte temperature.**  
High temperature resistant.



**IMPIEGO**  
**APPLICATIONS**

Tubo in silicone trasparente idoneo alla mandata di liquidi alimentari secondo FDA (CFR 21 cap. 177.2600) ove richiesta resistenza ad alte temperature.

Transparent silicone hose suitable for the delivery of food liquids according to FDA (CFR 21 cap. 177.2600) where is necessary an high temperature resistance.



**STRUTTURA**  
**BODY**

<b>A</b>	<b>Materiale Material</b>	Silicone atossico. Neutral non toxic silicone hose.
<b>B</b>	<b>Inserti Reinforcement</b>	---
<b>C</b>	<b>Copertura Cover</b>	Silicone traslucido. Translucent silicone.
	<b>Superficie Surface</b>	Trasparente. Transparent.



**FASCETTE E COLLARI STRINGITUBO CONSIGLIATE**  
**RECOMMENDED CLAMP/COLLAR**

STF - Fascette a vite Hose clamps with screw (pag. 208-212)

SGT - Fascette pinzabili Stepp less (pag. 221)

SBS - Fascette bifilari a molla Double wire spring (pag. 222)



mm	mm	bar	bar	bar	gr/mt	mm	m
2	4	-	-	-	12	-	100
3	5	-	-	-	16	-	100
3	6	-	-	-	26	-	100
4	6	-	-	-	20	-	100
4	7	-	-	-	32	-	100
4	8	-	-	-	46	-	100
5	8	-	-	-	38	-	100
5	9	-	-	-	54	-	100
5	10	-	-	-	75	-	100
6	8	-	-	-	27	-	100
6	9	-	-	-	45	-	100
6	10	-	-	-	62	-	100
6	12	-	-	-	103	-	100
7	10	-	-	-	51	-	50
7	11	-	-	-	69	-	50
8	10	-	-	-	37	-	50
8	12	-	-	-	77	-	50
8	13	-	-	-	101	-	50
8	14	-	-	-	127	-	50
9	12	-	-	-	63	-	50
10	14	-	-	-	92	-	50
10	16	-	-	-	111	-	50
12	16	-	-	-	112	-	50
12	18	-	-	-	177	-	50
14	18	-	-	-	123	-	50
15	20	-	-	-	172	-	50
18	24	-	-	-	247	-	25
22	26	-	-	-	194	-	25



**NORME NORMS:**  
REG. UE 10/2011 FOR SIMULANT TYPE A-B-C  
ISO 1307

**DICHIARAZIONE DI CONFORMITÀ DISPONIBILE**  
DECLARATION OF COMPLIANCE IS AVAILABLE



**-60°C / +150°C**  
con picchi fino a  
with peaks up to  
+200°C

**-76°F / +302°F**  
con picchi fino a  
with peaks up to  
+392°F