



IMPIEGO APPLICATIONS

Industria in genere	Industry in general
Macchine agricole	Agriculture machine
Edilizia	Construction
Ciclomotori	Motorcycles
Automotive	Automotive



DESCRIZIONE DESCRIPTION

Le fascette con anello interno SAE tipo F WDB sono particolarmente indicate per i circuiti di raffreddamento. L'anello interno garantisce una tenuta sicura su tubi in materiali morbidi creando un effetto oring tra fascetta, tubo e portagomma.

For air to air and coolant applications. The inner shield provides superb sealing characteristics and is safe for all soft hoses. It can also be found in the marine, agriculture, construction and off-highway markets.



MATERIALE MATERIAL

Banda Band	Acciaio inossidabile Stainless steel AISI 304
Cassetto Housing	Acciaio inossidabile Stainless steel SERIES 300
Vite Screw	Acciaio inossidabile Stainless steel SERIES 300

LARG. NASTRO BAND WIDTH	DIAM. DIAM.	SPESSORE THICKNESS	COPPIA DI SERRAGGIO RACCOMANDATA RECOMMENDED TIGHTENING TORQUE (PAG. 228)	SCATOLE BOX
A mm	B mm	C mm	Nm	pz/nrm

16
mm

WDB015034	16,51	15,9-34,9	8	3,4-4,5	400
WDB017041	16,51	17,5-41,4	8	3,4-4,5	400
WDB023047	16,51	23,8-47,6	8	3,4-4,5	400
WDB030054	16,51	30,2-54,0	8	3,4-4,5	400
WDB036060	16,51	36,5-60,3	8	3,4-4,5	300
WDB042066	16,51	42,9-66,7	8	3,4-4,5	300
WDB049073	16,51	49,2-73,0	8	3,4-4,5	300
WDB055079	16,51	55,6-79,4	8	3,4-4,5	300
WDB061085	16,51	61,9-85,7	8	3,4-4,5	300
WDB068092	16,51	68,3-92,1	8	3,4-4,5	300
WDB074098	16,51	74,6-98,4	8	3,4-4,5	200
WDB087111	16,51	87,3-111,1	8	3,4-4,5	200
WDB100123	16,51	100,0-123,8	8	3,4-4,5	200
WDB112136	16,51	112,7-136,5	8	3,4-4,5	200