



- **PROFILO ESTRUSO ESPANSO**
EXTRUDED FOAM PROFILE



CAMPI D'IMPIEGO APPLICATIONS

- Automotive
- Riscaldamento-condizionamento
- Ferroviario
- Costruzioni (infissi-isolamento)
- Aerospaziale
- Navale
- Macchine movimento terra
- Macchine Utensili
- Elettrico
- Fotovoltaico
- Energia Eolica
- Energia Elettrica
- Sportivo
- Anti-infortunistica
- Automotive
- Heating-conditioning
- Railway
- Construction (fixtures-insulation)
- Aerospace
- Naval
- Constructions Equipment
- Machine tools
- Electric
- Photovoltaic
- Wind energy
- Electric energy
- Sporty
- Safety



FORMATI DISPONIBILI AVAILABLE FORM



Rocchetto / Reel



Matassa / Coil*

* A seconda del diametro.
* According to the diameter.



SPECIFICHE TECNICHE TECHNICAL DATA SHEET

	NORME / STANDARD	VALORE / RESULTS
Tipologia Materiale Material Base		EPDM
Struttura cellulare Cells structure		Cellule Chiuse Closed Cells
Colore Color		Nero / Black
Densità Density	ISO 845	0,45 ± 1 g/cm ³
Tolleranze dimensionali Dimension tolerances	ASTM D-1056	
Compressione Compression Set	23°C, 50% after 22h	20%
Durezza Hardness		15 ± 5 Sh A
Temperatura Temperature	Costante / Constant	-35°C / +110°C
Resistenza a Resistance to		
Agenti atmosferici / Weathering		Molto buona / Very good
Ozono e UV / Ozon and UV		Molto buona / Very good
Usura / Aging		Molto buona / Very good
Fiamme / Flame		Giusta / Fair
Benzina / Petrol		Bassa / Low
Oli minerali e grassi / Mineral oil and greases		Bassa / Low
Oli vegetali / Vegetable oil		Soddisfacente / Satisfactory
Chetone e acidi / Ketone and acids		Soddisfacente / Satisfactory
Lisciva / Lye		Soddisfacente / Satisfactory